




- OPP 0100**
Power supply 100 W
- for OxX-series
 - 100 W output power
 - 11 separate outputs
 - 2A current limit on all outputs
 - 7.5V outputs
 - Input voltage range 94-264V
 - Mounting in 19" base unit (OBU 0100)
 - Easy installation
 - High efficiency



- OSP 0110**
Power supply 15 W
- for single OxX-series module
 - Max 25 W output power, 15W continuously
 - 3.2A current limit
 - 7.5V output
 - Input voltage range 94-264V
 - High efficiency



- OBU 0100**
Base unit
- A base unit for OxX-series modules
 - Fits 7 modules + power supply (power supply for max. 5 modules)



- ODCC 100**
DC-cable for OPP 0100
- Cabling for connection between power supply OPP 0100 and modules in OxX-series. (approx. length 80 cm)



- OWM 0200**
Wall mount kit
- For OxX-series modules
 - Easy installation of single units



- OAVC 100**
Audio/video cable



OALC 025
ASI cable 250 mm
BNC - BNC



OALC 100
ASI cable 1000 mm
BNC - BNC



OCP 0220
Cover plate 20 mm



OCP 0250
Cover plate 50 mm

WISI Communications GmbH & Co. KG

Empfangs- und Verteiltechnik
Wilhelm-Sihn-Straße 5-7
75223 Niefern-Öschelbronn, Germany

Telefon +49 72 33-66-280 Fax -3 50
export@wisi.de
www.wisi.de

