




... a link to the future



Product Information

DM 51 1010 / DM 51 1015 / DM 51 1020




Indoor Satellite Tap offs



- 3 types with different tap loss values
- Frequency range from 5 to 2400 MHz
- Directional coupler
- Screening factor >85 dB, Class A
- DC-Bypass 1A / 30 V

DM 51 1010 / 1015 / 1020 Satellite Tap offs

Type		DM 51 1010 1-way tap off	DM 51 1015 1-way tap off	DM 51 1020 1-way tap of
Specifications	Insertion loss 5-2400 MHz	1.5-2.5 dB	1-2.0 dB	0.7-1.8 dB
	Tap loss 5-2400 MHz	11 dB	15 dB	20 dB
	Directional attenuation 5-40 MHz	32 dB	35 dB	40 dB
	Directional attenuation 40-1000 MHz	25 dB	30 dB	32 dB
	Directional attenuation 1000-2400 MHz	22 dB	25 dB	28 dB
	Isolation 5-2400 MHz	-	-	-
	Screening factor	>85 dB Class A	>85dB Class A	>85 dB Class A
	DC-Bypass IN-OUT	yes	yes	yes
	Dimensions / mm	52x50x18	52x50x18	52x50x18
	Packing unit	5 pieces, bag		
	Shipping package	25 pieces 9,8 dm³, 3,6 kg		



Technical Modifications reserved. WISI cannot be held liable for any printing error!
083 883 / 09. 06



WISI Communications GmbH & Co. KG
Empfangs- und Verteiltechnik
P.O. BOX 1220
75219 Niefern-Oeschelbronn, GERMANY
Phone +49/(0)7233/66-280
Fax +49/(0)7233/66-350
www.wisi.de
export@wisi.de

... a link to the future